

TEQOYA SAS TEST REPORT

SCOPE OF WORK

< Air Ionizer- [TeqAir200]>

REPORT NUMBER

190314057GZU-001

ISSUE DATE

29-March-2019

PAGES

6

DOCUMENT CONTROL NUMBER

General-HA-001a (23-October-2018) © 2018 INTERTEK





Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD, Guangzhou, China

Telephone: 86-20-8213 9688 Facsimile: 86-20-3205 7538

www.intertek.com

Applicant Name : TEQOYA SAS Report Date: 29 March, 2019

Applicant Address : 14 Avenue Jean Perrin-92330 Sceaux-FRANCE

Sample Description:

Product Name : Air Ionizer

Brand Name : --

Model No. : TeqAir200

Electrical Rating : 100-240V~, 50/60Hz, 0,3A for adaptor; 12Vdc, 0,3A for product.

No. of Samples : 1

Date Received : 14 March 2019

Date Test Conducted : 14 March 2019 to 19 March, 2019

Test specification:

Test Requested :Ozone Test

Test Method (standards): Refer to Clause 32 of IEC 60335-2-65:2002 + A1: 2008 + A2: 2015 and EN 60335-2-

65:2003+A1:2008+A11:2012

Test Result : See Appendix A test result on page 4

Conclusion : The submitted sample complies with the above safety standards / requirements

Prepared by: Reviewed by:

Kevin Ye Rose Zhao

Engineer Technical Manager

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Version: 23-October-2018 Page 2 of 6 General-HA-001a



al Quality, Assured. Intertek Report: 190314057GZU-001

Notes:

1. This report does not imply the compliance of all requirements of above standards. The mentioned test is only partial checking according to above standards.

- 2. This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- 3. Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

Version: 23-October-2018 Page 3 of 6 General-HA-001a



I Quality, Assured. Intertek Report: 190314057GZU-001

Appendix A:

Test condition:

The test is carried out in a room without openings having dimensions of $2.5 \text{ m} \times 3.5 \text{ m} \times 3.0 \text{ m}$, the walls being covered with polyethylene sheet. The appliance is positioned in accordance with the instructions. Appliances used on a table are placed in the centre of the room approximately 750 mm above the floor.

The room is maintained at approximately $25\,\mathrm{C}^\circ$ and 50% relative humidity. The appliance is supplied at rated voltage for 24 h, removable filters being removed if this is more unfavourable.

The ozone sampling tube is to be located in the air stream 50 mm from the air outlet of the appliance. The background ozone concentration measured prior to the test is subtracted from the maximum concentration measured during the test.

Test result:

During the test, the maximun ozone concentration was measured **0,23** PPB, not exceed **50** PPB.

Version: 23-October-2018 Page 4 of 6 General-HA-001a